

DIMENSIONS OF THREE PHASE MOTORS

Foot mounted B3 (IM1001) up to frame size 180

type	P	num-ber Of pole	flange dimensions in mm										overall dimensions in mm										
			A	B	C	CA	H	K	Pg	Shaft extension in mm				AA	AB	AC	BA	BB	HA	HD	L	LC	
										D/ DA	E/ EA	F/ FA	GA/ GC										
DK56	A	2-4	90	71	36	66.5	56	5.8	13.5	9j6	20	3h9	10.2	30	110	117	-	92	7	164	188	213.5	
	B	2-4				74.5															196	221.5	
DK63	A	2-4	100	80	40	67	63	7	13.5	11j6	23	4h9	12.5	36	124	126	-	106	8.5	165	202	233	
	B	2-4				79															214	245	
DK71	A	2-8	112	90	45	74	71	7	13.5	14j6	30	5h9	16	45	142	141	-	116	8	173	231	269	
	B	2-8				83															240	273	
DK80	A	2-8	125	100	50	76	80	10	13.5	19j6	40	6h9	21.5	55	160	157	-	130	9	195	255	306	
	B	2-8				93															272	323	
DK90	S	2-8	140	100	56	111	90	10	13.5	24j6	50	8h9	27	45	170	180	38	126	10	232	306	367	
	L	2-8		125													43	151			331	392	
DK100 L	T	2-8	160	140	63	126	100	12	13.5	28j6	60	8h9	31	48	196	206	48	170	15	255	374	449	
DK112 M	T	2-8	190	140	70	124	112	12	21	28j6	60	8h9	31	54	220	233	48	170	15	280	383	454	
DK13 2	S	2A,4-8	216	140	89	143	132	12	21	38k6	80	10h9	41	71	274	263	63	180	18	313	440	532	
	S	T		2B		140											183	180			180	480	572
	M			4-8		178											145	218			480	572	
DK16 0	M	2-8	254	210	108	210	160	15	29	42k6	110	12	45	60	300	323	-	256	20	370	630	748	
	L	2-8		254														300			674	792	
DK18 0	M	2-4	279	241	121	243	180	15	29	48k6	110	14	51.5	70	350	360	-	320	26	408	705	825	
	L	4-8		279		205												705			825		

Overall dimensions are subject to change without notice.