

DIMENSIONS OF THREE PHASE MOTORS

Foot mounted B3 (IM1001) from frame size 200 up to 355

Type	P	nu m- ber Of pol e	mounting dimensions in mm										overall dimensions in mm											
			A	B	C	CA	H	K	Pg	Shaft extension in mm				AA	AB	AC	AD	BA	BB	HA	HD	L	LC	
										D/D A /m6	E/ EA	F/A /h9/	GA/ GC											
DK200	L	C	2-8	318	305	133	265	200	19	36	55	110	16	59	80	400	450	355	100	378	32	485	810	923
DK225	S	C	4-8	356	286	149	290	225	19	36	60/55	140/110	18/16	64/59	85	445	505	375	110	355	34	535	860	975
	M	2	311		60/55						140/110	18/16	64/59	380						855			970	
	M	4-8	311		60/55						140/110	18/16	64/59	380						885			1000	
DK250	M	C	2	406	349	168	335	250	24	42	60/55	140/110	16/14	64/59	90	495	536	415	120	420	36	590	980	1102
	M	4-8	65/60								140/140	18/16	69/64	1132										
DK280	S	C	2	457	368	190	350	280	24	42	65/60	140/140	18/18	69/64	100	560	620	450	165	520	40	660	1040	1188
	S	4-8	75/65								20/18		79.5/69											
	M	2	65/60								18/18		69/64											
	M	4-8	75/65								20/18		79.5/69											
DK315	S	C	2	508	406	216	421	315	28	M7 6x3	65/65	140/140	18/18	69/69	105	610	620	450	190	560	46	695	1180	1323
	S	4-8	80/65								170/140	22/18	85/69	1210									1353	
	M	2	65/65								140/140	18/18	69/69	1180									1323	
	M	4-8	80/65								170/140	22/18	85/69	1210									1353	
	M	4-8	80/65								170/140	22/18	85/69	1210									1353	

Overall dimensions are subject to change without notice.