

DIMENSIONS OF THREE PHASE MOTORS

Foot and flange mounted (B35) up to frame size 315

Type	P	number Of Pole	Mounting dimensions in mm														Shaft extension in mm					
			A	B	C	CA	H	K	Pg	flange dimensions						D/DA	E/EA	F/FA /h9 /	GA/GC			
										PN Type DIN	M	N /j6/	P	LA	S					T		
DLK56	A/B	2-4	90	71	36	66/24 74	56	58	13.5	FF100	10	80	120	8	7	4	3	9j6	20	3	10.2	
DLK63	A/B	2-4	100	80	40	78	63	7	13.5	FF115	15	95	140	10	10	4	3.5	11j6	23	4	12.5	
DLK71	A/B	2-8	110	90	45	74 83	71	7	13.5	FF130	13	110	160	9	10	4	3.5	14j6	30	5	16	
DLK80	A/B	2-8	120	100	50	76 93	80	10	13.5	FF165	16	130	200	10	12	4	3.5	19j6	40	6	21.5	
DLK90	S/L	2-8	140	100 125	56	111	90	10	13.5	FF165	16	130	200	10	11	4	3.5	24j6	50	8	27	
DLK100	L	2-8	160	140	63	126	100	12	13.5	FF215	21	180	250	11	14	4	4	28j6	60	8	31	
DLK112	M	2-8	190	140	70	124	112	12	21	FF215	21	180	250	11	14	4	4	28j6	60	8	31	
DLK132	S	2A,4-8	210	140	89	143	12	21	FF265	26	230	300	13	14	4	4	38K6	80	10	41		
	S	2B		140		183																
	M	4-8		178		145																
DLK160	M/L	2-8	250	210 254	108	210	160	15	29	FF300	30	250	350	13	19	5	5	42K6	110	12	45	
DLK180	M/L	2-4	270	240 279	120	243 205	180	15	29	FF300	30	250	350	13	19	5	5	48K6	110	14	51.5	
DLK200	L	2-8	310	300 350	130	265	200	19	36	FF350	35	300	400	16	18	4	5	55	110	16	59	
DLK225	S	4-8	350	280	140	290	220	19	36	FF400	40	350	450	18	18	8	5	60/55	140/110	18/16	64/59	
	M	2		310														55/48		18/14	59/51	
	M	4-8		310														60/55		18/16	64/59	
DLK250	M	2	400	340	160	335	250	24	42	FF500	50	450	550	19	18	8	5	60/55	140/110	18/16	64/59	
	M	4-8																65/60		140/140	18/18	69/64
DLK280	S	2	450	360	190	350	280	24	42	FF500	50	450	550	20	18	8	5	65/60	140/140	18/18	69/64	
	S	4-8		360		350												75/65		20/18	79.5/69	
	M	2		419		299												65/60		18/18	69/64	
	M	4-8		419		299												75/65		20/18	79.5/69	
DLK315	S	2	580	400	210	421	310	28	M76 X3	FF600	60	550	660	22	22	8	6	65/65	140/140	18/18	69/69	
	S	4-8		400		421												80/65		170/140	22/18	85/69
	M	2		457		370												80/65		140/140	18/18	69/69
	M	4-8		457		370												80/65		170/140	22/18	85/69

type	P	num-ber Of pole	Overall didmensions in mm										L	LC
			AA	AB	AC	AD	BA	BB	HA	HD				
DLK56	A/B	2-4	30	110	112/108 112	74	-	92	7	154	188/149	213/171		
DLK63	A/B	2-4	36	124	126	74	-	97	8.5	165	202	233		
DLK71	A/B	2-8	45	142	134	70	-	116	8	178	214	245		
DLK80	A/B	2-8	55	160	150	70	-	130	9	195	231	269		
DLK90	S/L	2-8	45	170	180	-	38 43	126 151	10	232	240	278		
DLK100	L	2-8	48	196	206	-	48	170	15	255	255	306		
DLK112	M	2-8	54	220	233	-	48	170	15	280	272	323		
DLK132	S	2A,4-8	71	274	263	-	63	180	18	313	440	532		
	S	2B					63	180			480	572		
	M	4-8					79	218			480	572		
DLK160	M/L	2-4	60	300	318	195	-	256 300	20	370	630	748		
DLK180	M/L	2-4	70	350	358	210	-	320	26	408	674	792		
DLK200	L	2-8	80	400	398	355	100	378	32	485	810	923		
DLK225	S	4-8	85	445	505	375	110	355	34	535	860	975		

	M		2						380			855	970
	M		4-8						380			885	100
DLK250	M	C	2,4-8	90	495	536	415	120	420	36	590	980	1102,1132
DLK280	S,M	C	2,4-8	100	560	620	450	165	520	40	660	1040	1188
DLK315	S,M	C	2,4-8	105	610	620	450	190	560	46	695	1180,1210	1323,1353

Overall dimensions are subject to change without notice.