

DIMENSIONS OF THREE PHASE MOTORS

Face flange B5/VI (IM3011) up to frame size 180

type	P	num-ber Of pole	mounting dimensions in mm											Overall dimensions in mm					
			Pin Type DIN	Shaft extension in mm							Shaft extension in mm				AC	HB	L	LC	
				M	N /j6 /	P	LA	S	T	Pg	D/ DA	E/ EA	F/FA /h9/	GA/ GC					
DVK56	A	B	2-4	FF100	100	80	120	8	7.0	3.0	13.5	9j6	20	3	10.2	117	96	188	213/171
	B		2-4															196	221
DVK63	A	B	2-4	FF115	115	95	140	9	10.0	3.0	13.5	11j6	23	4	12.5	126	100	202	233
	B		2-4															214	245
DVK71	A	B	2-8	FF130	130	110	160	9	10.0	3.5	13.5	14j6	30	5	16.0	141	107	231	269
	B		2-8															240	278
DVK80	A	B	2-8	FF165	165	130	200	10	12.0	3.5	13.5	19j6	40	6	21.5	157	115	255	306
	B		2-8															272	323
DVK90	S	T	2-8	FF165	165	130	200	10	11	3.5	13.5	24j6	50	8	27.0	180	142	306	367
	L		2-8															331	392
DVK100 L		T	2-8	FF215	215	180	250	11	14	4.0	13.5	28j6	60	8	31.0	206	155	374	449
DVK112 M		T	2-8	FF215	215	180	250	11	14	4.0	21.0	28j6	60	8	31.0	233	168	383	454
DVK13 2	SA	T	2A,4-8	FF265	265	230	300	13	14	4.0	21.0	38k6	80	10	41.0	263	181	440	532
	SB		2B															480	572
	M		4-8															480	572
DVK16 0	M	I	2-8	FF300	300	250	350	13	19	5.0	29.0	42k6	110	12	45.0	323	210	630	748
	L		2-8															674	792
DVK18 0	M	I	2-4	FF300	300	250	350	13	19	5.0	29.0	48k6	110	14	51.5	360	228	705	825
	L		4-8																

Overall dimensions are subject to change without notice.